


REVISIONS					
P	LTR	DESCRIPTION	DATE	DWN	APVD
A		NEW RELEASE PER ECO-14-013277	08-27-14	DM	DM



3. PART NO. HD30-24BT-BK
2. TEMPERATURE RATING: -29°C TO +100°C [-20°F TO +212°F]
1. THIS PART IS USED ON
 HDP24-24-XXX RECEPTACLES
 HDP26-24-XXX PLUGS
 HD34-24-XXX RECEPTACLES
 HD36-24-XXX PLUGS
 WHERE XXX IS PIN ARRANGEMENTS. SEE INDIVIDUAL CUSTOMER DRAWINGS

2014

RELEASED FOR PUBLICATION

ALL RIGHTS RESERVED.

© COPYRIGHT 2014 BY TE CONNECTIVITY

THIS DRAWING IS UNPUBLISHED.

DIMENSIONS: MM [INCH]	DWN	D. MEYER 27AUG2014	MATERIAL	PVC	FINISH	BLACK
	CHK	I. GRANTCHAROVA 27AUG2014	TE Connectivity			
TOLERANCES UNLESS OTHERWISE SPECIFIED:	APVD	D. MEYER 27AUG2014				
0 PLC ±	PRODUCT SPEC	NAME				BOOT, SIZE 24
1 PLC ±	APPLICATION SPEC	HD30/HDP20 SERIES				
2 PLC ± 0.63 [.025]		SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO	
3 PLC ±	WEIGHT	16.50 g	A 4	4AFU8	© = HD30-24BT-BK	-
4 PLC ±	Customer Drawing				SCALE	NONE
ANGLES ± 5°					SHEET	1 OF 1
					REV	A