MADE IN PRC

Product Description:

- Wireless dual lights output to make work easy.
- Ultra slim light bar for narrow place.
- Built-in hook and magnet for hands free.
- IK08 impact resistance for outdoor and rugged use.
- Battery life indicator to show remaining capacity of light.
- 180° foldable design for multi-angle light output satisfied with different environment.
- With dimming function for main light, press the button on hold to support dimming function.
- Switch sequence : spot light main light off @first button; double sides light on off @second button.

Specifications:

Charger Specification: Charging Voltage/Current: Battery Specification: Time of Charging(via Type-C): Time of Charging(via wireless pad): Time of Discharging:

Brightness:

CRI:
Color Temperature:
Working Temperature:
Storage Temperatur:

AC100-240V 50/60HZ 5V 1A 3.7V 4400mAh Li-ionApproximately 4 hours Approximately 6.5 hours Approximately 3 hours @first level Approximately 6 hours @second level Approximately 1000lumen @first level Approximately 500lumen @second level \geq 70Ra $5500\sim6500K$ $-10\sim40$ C $-20\sim50$ C

Battery treatment/charging:

- Charge the battery for at least 8 hours before first use
- Green indicator on lamp flashing: charging
- All green indicators light up on lamp means charging completed
- Do not leave battery in full discharged condition.
- Recharge the work light at least once in every 30 days
- Use original charger (output 5V /1A) , which can charge on wireless pad.



- Wear safety goggles. (User and bystander)
- Avoid looking directly into the beam

Warning:

- Do not use the lamp near open flames
- Always fully charge to extend battery life
- Do not cover the lens during the operating to prevent against overheating
- Do not contaminate the lens with organic solvents
- Take care to position the light and stand in a careful manner, to ensure the light is properly supported by the stand.



