PRODUCT INFORMATION

Description 12V DOT/ECE LED Fog Light

 Height
 48.40 mm / 1.91 in

 Width
 150.40 mm / 5.92 in

 Depth
 63.00 mm / 2.48 in

ShapeRectangularOuter Lens MaterialPolycarbonate

Outer Lens Color Clear

Housing Material Die-Cast Aluminum

Housing ColorBlackBezel ColorBlack

Mounting Hardware Description (x2) 5/16-18 x 1.00" Mounting Bolt

Mounting Type Pedestal/Pendant **Minimum Operating** -40 °C / -40 °F

Temperature

Maximum Operating 65 °C / 149 °F

Temperature


Connector or WiringIntegrated 2-Pin Deutsch ConnectorMating Connector2-Pin Deutsch Weather-Proof Plug

(DT06-2S)

Product Weight 0.80 lbs / 0.36 kgs **Shipping Weight** 1.20 lbs / 0.54 kgs



PRODUCT DIMENSIONS



ELECTRICAL SPECIFICATIONS


Input Voltage12V DCOperating Voltage10-18V DC

Transient Spike Protection 150V Peak @ 1 HZ-100 Pulses

Red WirePowerBlack WireGround

Current Draw 0.55A @ 10V DC (Fog) 0.88A @ 12V DC (Fog)

1.10A @ 18V DC (Fog)





REGULATORY STANDARDS COMPLIANCE







ECE Reg 19

IEC IP69K

SAE J583







Buy America Standards Eco Friendly **SAE J578**

Tested to ECE Reg. 10 (Radiated Emissions only)

PHOTOMETRIC SPECIFICATIONS


Raw Lumen Output 800 250

Effective Lumen Output

Candela Output 6,700

Beam Pattern(s) Forward Lighting - Fog

Nominal LED Color 4750 K **Temperature**



APPLICATIONS




















PRODUCT WARNINGS

For California residents:

▲ WARNING: Cancer and reproductive harm - www.P65Warnings.ca.gov.

AVERTISSEMENT: Cancer et effet nocif sur la reproduction - www.P65Warnings.ca.gov.

RELATED PRODUCTS



Part Number 1603511 12-24V LED Driving Light



Part Number
1603521
12-24V LED Driving
Light with Flood Beam
Pattern



Part Number 1603603 12V DOT/ECE LED Fog Light - 2 Light Kit

